




Vasario™ Series

Product Specifications

Electronically Operated (Media)

1915 Model




Dimensions:
(width x depth x height)

18.8 x 15.2 x 4.3 inches
478 x 386 x 110 mm

Shipping weight: 22 lbs
10 kg

1618 Model




Dimensions:
(width x depth x height)

16.2 x 18.3 x 4.3 inches
411 x 466 x 110 mm

Shipping weight: 21 lbs
9.5 kg

1616 Model




Dimensions:
(width x depth x height)

16.2 x 16.3 x 4.3 inches
411 x 415 x 110 mm

Shipping weight: 19 lbs
8.6 kg

1313 Model




Dimensions:
(width x depth x height)

13.1 x 13.1 x 3.93 inches
335 x 335 x 100 mm

Shipping weight: 13 lbs
5.9 kg

Electronically Operated (Non-Media)

1416 Model




Dimensions:
(width x depth x height)

13.8 x 16.3 x 4.0 inches
351 x 415 x 102 mm

Shipping weight: 16 lbs
7.3 kg

Manually Operated (Non-Media)

1616 Model




Dimensions:
(width x depth x height)

16.2 x 16.3 x 4.3 inches
411 x 415 x 110 mm

Shipping weight: 19 lbs
8.6 kg

Manually Operated (Non-Media) Continued

1416 Model



Dimensions:
(width x depth x height)

13.8 x 16.3 x 4.0 inches
351 x 415 x 102 mm

Shipping weight:

16 lbs
7.3 kg

Features

- Numerous till configurations available. Contact your APG representative for options
- Available in Black and All-White, with either a painted or stainless steel drawer front (*stainless not available for manually operated drawers*)
- Electronic drawers tested to last beyond 1 million transactions
- Manual drawers tested to last to 300,000 transactions
- Under till storage area
- Lower cost solution provides value in lower traffic retail environments
- Four function lock
- Closed and latched drawer status switch (*not available in manual*)
- Random keying is standard, other lock and key options available

Available Interfaces

101	Manually Operated Drawer***	554A	USBPro™ HID End Node**
320	MultiPRO® 24 volt *	XXX	Other interface numbers indicate a custom interface
320-1	MultiPRO® 24 volt w/ CD-101A Cable		
420	MultiPRO® II 12 volt*		
484A	SerialPRO® II**		

* Requires detachable cable sold separately.

** Not available in 1313 size.

*** Only available for 1416 and 1616 sizes.

Refer to APG's Connectivity Guide at www.cashdrawer.com/connectivity-guide for interface cable detail.

Operating Environment

Storage Temperature	-30°C to +50°C (-22°F to +122°F)	Relative Humidity	10% to 95%
Operating Temperature	0°C to +40°C (+32°F to +104°F)	<i>(non-condensing)</i>	

Accessories

See our Standard Accessories Guide or contact your APG representative for options.

1. Tills
2. Locking till covers
3. Weighable coin cups
4. Under counter mounting brackets

Warranty

Three (3) year limited warranty. A full warranty statement is available online at www.cashdrawer.com/warranty.

Contact Us



APG Cash Drawer, LLC
5250 Industrial Blvd NE
Minneapolis, MN 55421



+1 (763) 571-5000



sales@us.cashdrawer.com