



Series 4000

Product Specifications

1317 Model




Dimensions:
(width x depth x height)
Height without feet

13.3 x 17.2 x 4.2 inches
337 x 437 x 107 mm
4.1 inches or 104 mm

Shipping weight: 22 lbs
10.0 kg

1816 Model




Dimensions:
(width x depth x height)
Height without feet

18.0 x 16.7 x 4.2 inches
457 x 424 x 107 mm
4.1 inches or 104 mm

Shipping weight: 30 lbs
13.6 kg

1820 Model




Dimensions:
(width x depth x height)
Height without feet

18.8 x 20.0 x 4.2 inches
478 x 508 x 107 mm
4.1 inches or 104 mm

Shipping weight: 31 lbs
14.1 kg

1821 Model



Dimensions:
(width x depth x height)
Height without feet

18.8 x 21.0 x 4.2 inches
478 x 533 x 107 mm
4.1 inches or 104 mm

Shipping weight: 32 lbs
14.5 kg

Additional Features: Rear of cash drawer has cable storage area with a removable back panel.

Features

1317 Model

- 4 bill, 4 coin fixed assembly till standard
- Single media slot
- Industrial grade, steel ball bearing slides
- Tested to last beyond 4 million transactions
- Under till storage area
- Available in Black and Cloud White, with either a painted or stainless steel drawer front
- Closed and latched drawer status switch
- Four function lock
- Random keying from 10 lock codes is standard, other lock and key options are available

Features

1816, 1820, and 1821 Models

- Numerous till configurations available. See our Performance Accessories brochure or contact your APG representative for options
- Dual media slots standard
- Industrial grade, steel ball bearing slides
- Tested to last beyond 4 million transactions
- Under till storage area
- Available in Black and Cloud White, with either a painted or stainless steel drawer front
- Closed and latched drawer status switch
- Four function lock
- Random keying from 10 lock codes is standard, other lock and key options are available

Available Interfaces

320	MultiPRO® 24 volt *	480A	NetPRO® Ethernet Interface**
320-1	MultiPRO® 24 volt w/ CD-101A Cable	XXX	Other numbers indicate the DirectPRO® hardwired or a custom interface
420	MultiPRO® II 12 volt *		
520	MultiPRO® III Dual 12/24 volt *		
484A	SerialPRO® II		
554A	USBPro™ HID End Node		

* Requires detachable cable sold separately.
** Numerous Ethernet options, see NetPRO® brochure.
Refer to APG's Connectivity Guide at www.cashdrawer.com/connectivity-guide for interface cable detail.

Operating Environment

Storage Temperature	-30°C to +50°C (-22°F to +122°F)	Relative Humidity	10% to 95%
Operating Temperature	0°C to +40°C (+32°F to +104°F)	(non-condensing)	

Accessories

See our Performance Accessories Guide or contact your APG representative for options.

1. Tills
2. Locking till covers
3. Weighable coin cups
4. Under counter mounting brackets

Warranty

Limited Lifetime Warranty (online registration required). Without registration 5 year limited warranty applies. Register online at: www.cashdrawer.com/warranty.

Contact Us



APG Cash Drawer, LLC
5250 Industrial Blvd NE
Minneapolis, MN 55421



+1 (763) 571-5000



sales@us.cashdrawer.com