

Vasario[™] Series **Product Specifications**

A Cost Effective Solution for Low Volume Environments

Each member of the Vasario™ cash drawer family is competitively priced and includes features, such as multifunction locks and drawer status reporting, found in more expensive cash drawers. A variety of models with a wide range of size, style, color, interface and till configuration options are available to meet your specific requirements.

Electronically Operated (Media)

| ٦ | O. | 15 | M | ٨ | _ |
|---|----|-----|-----|---|---|
| | 9 | 13) | IVI | • | - |



Dimensions: (width x depth x height) 18.8 x 15.2 x 4.3 inches 478 x 386 x110 mm

Shipping weight: 22 lbs

10 kg

1618 Model




Dimensions: (width x depth x height) 16.2 x 18.3 x 4.3 inches 411 x 466 x110 mm

Shipping weight: 21 lbs

9.5 kg

1616 Model



Dimensions: (width x depth x height) 16.2 x 16.3 x 4.3 inches 411 x 415 x 110 mm

Shipping weight: 19 lbs

8.6 kg

1313 Model



Dimensions:

(width x depth x height)


13.1 x 13.1 x 3.93 inches 335 x 335 x 100 mm

Shipping weight: 13 lbs

5.9 kg

Electronically Operated (Non-Media)

1416 Model



Dimensions: (width x depth x height) 13.8 x 16.3 x 4.0 inches 351 x 415 x 102 mm

Shipping weight: 16 lbs

7.3 kg

M-43-111 Rev. I

Manually Operated (Non-Media)

1616 Model



Dimensions: (width x depth x height) 16.2 x 16.3 x 4.0 inches 411 x 415 x 110 mm

Shipping weight: 19 lbs

8.6 ka

1416 Model



Dimensions: (width x depth x height) 13.8 x 16.3 x 4.0 inches 351 x 415 x102 mm

Shipping weight: 16 lbs

7.3 kg

Features

- Numerous till configurations available. Refer to www. apgsolutions.com/configurator/vasario for Accessories Guide.
- Available in Black and All-White, with either a painted or stainless steel drawer front (stainless not available for manually operated drawers)
- Electronic drawers tested to last beyond 1 million transactions
- Manual drawers tested to last to 300,000 transactions

- Under till storage area
- The cost effective choice for medium traffic retail enviornments that does not sacrifice quality or dependability.
- Four function lock
- Closed and latched drawer status switch (not available in manual)
- Random keying is standard, other lock and key options available

Interfaces

101 Manually Operated Drawer*** 554A USBPro™ HID End Node**

320 MultiPRO® 24 volt * XXX Other interface numbers indicate a custom interface

320-1 MultiPRO® 24 volt w/ CD-101A Cable

420 MultiPRO® II 12 volt* A SerialPRO® II** 484

Refer to APG's Connectivity Guide at www.apgsolutions.com/configurator/ vasario for interface cable detail.

Operating Environment

 -30° C to $+50^{\circ}$ C (-22° F to $+122^{\circ}$ F) Storage Temperature 0° C to +40 $^{\circ}$ C (+32 $^{\circ}$ F to +104 $^{\circ}$ F) **Operating Temperature**

Relative Humidity 10% to 95% (non-condensing)

Accessories

See our Standard Accessories Guide or contact your APG representative for options.

1. Tills 2. Latching, keyless till covers 3. Weighable coin cups 4. Under countemounting brackets

Warranty

Three (3) year limited warranty. A full warranty statement is available online at www.apgsolutions.com/warranty.

M-43-111 Rev. I

^{*} Requires detachable cable sold separately.

^{**} Not available in 1313 size.

^{***} Only available for 1416 and 1616 sizes.